

iT1-AM

Attachment Module for iT100

iT100



Smart card



Prox card



Supports Wi-Fi



Supports POE



iT1-AM

Specifications

Dimensions (W x H x D)	180mm x 41mm x 32mm (7.08" x 1.61" x 1.25") (included Install Plate)	Connectivity	Wi-Fi 802.11 b/g/n (optional)
Weight	0.39lbs (177g) (included Install Plate)	Certifications	CE, FCC, KC
Type	Attached Module	Temperature	Operating: 0 ~ 45°C (32 ~ 113°F) / Storage: -20 ~ 90°C (-4 ~ 194°F)
Power Input	Required POE+ (30W)	Humidity	5% to 95% non-condensing
Power Output	24 VDC / Max 1.2A		

iT1-AMD

RFID Card Reader	13.56MHz Multi-Protocol RFID ISO/IEC 14443A/B, MIFARE Classic, MIFARE Ultralight, MIFARE (UID Read Only), ISO/IEC 15693, Felica(JIS X6319-4)
------------------	---

iT1-AM4 / iT1-AMX

RFID Card Reader	125kHz HID Proxy RFID HID Prox, HID Prox II
------------------	--



Iris ID Systems, Inc.

8 Clarke Drive, Cranbury, NJ 08512, USA
Tel. +1-609-819-4747 Fax. +1-609-819-4736
www.irisid.com | sales@irisid.com



© 2021 Iris ID Systems, Inc. All rights reserved. Design and specification subject to change without notice.

IRIS ID AUTHORIZED RESELLER